



**Brown Davis Automotive Pty. Ltd.**

ABN: 72 657 573 544

*Copyright Brown Davis Automotive Pty. Ltd. This document contains confidential and Technical information the property of Brown Davis Automotive Pty. Ltd.*

**UGHDCRVR1**

**1**

Last edited: 21/10/2010

## **Underguard Part List and Installation Instructions**

*Underguard P/N: **UGHDCRVR1***

HONDA CRV  
REAR DIFF GUARD

Item	Description	Quantity	Part number	P	C
1	UNDERGUARD	1	UGHDCRVR1		
2	SET SCREW – HEX – M8 X 25mm – PLATED 8.8	2			
3	WASHER – FLAT PLATED – M8	2			
4	WASHER – SPRING PLATED – M8	2			
5	SET SCREW – HEX – M10 X 25mm – PLATED 8.8	2			
6	WASHER – PANEL PLATED – M10	2			
7	WASHER – SPRING PLATED – M10	2			
8	BOLT – HEX – M12 X 100mm – PLATED 8.8	1			
10	WASHER – FLAT PLATED – M12	2			
11	NUT – NYLOC PLATED – M12	1			
12	ROUND TUBE SPACER – 18mmID x 10mmI	2	SP-018-010		
13	RUBBER STRAP with LIPS	270mm			
14	HARD FOAM PADDING – 30mmWx 20mmH	165mm			
15	UNDERGUARD BRACKET – CURVED BRACKET	1	UB-UGHDCRVR1-a		
16	UNDERGUARD BRACKET – TWIN UPRIGHT BRACKET	1	UB-UGHDCRVR1-b		
17	KIT LIST	1			
18	BROWN DAVIS UNDERGUARD STICKER	1			

Packed by (P): \_\_\_\_\_

Checked by (C): \_\_\_\_\_

Date Packed: \_\_\_\_ / \_\_\_\_ / \_\_\_\_

PH: +61 (3) 9762 8722 FAX: +61 (3) 9762 9829  
47 Holloway Drive, Bayswater, Victoria, Australia 3153

**info@browndavis.com.au    www.browndavis.com.au**



**Brown Davis Automotive Pty. Ltd.**

ABN: 72 657 573 544

*Copyright Brown Davis Automotive Pty. Ltd. This document contains confidential and  
Technical information the property of Brown Davis Automotive Pty. Ltd.*

**UGHDCRVR1**

**2**

All Brown Davis Automotive Underguards are manufactured from 3.0 mm aluminised cold rolled steel to ensure maximum strength and durability. The aluminising gives protection against corrosion and the 3.0mm steel has been found to be sufficiently impact resistant to give the required protection to the vital components under your car.

Underguards are designed to not adversely affect the cooling requirements of your car, vent holes are strategically placed to allow sufficient airflow in to the engine bay in hot conditions. All Underguards are M.I.G. (Metal Inert Gas) welded to ensure the strongest possible structure and are strengthened where necessary to add further protection and impact capabilities. Where needed Underguard mounting bolt holes/bolt heads are protected with strategically placed steel shields.

In all cases, Brown Davis Underguards are designed with severe off road use in mind and are designed to protect against impact and damage sustained due to harsh conditions or coming into contact with terrain.

### **Installation Instructions**

1. Fit the twin upright bracket to the lower rear diff mount support with the supplied M12 fasteners and tube spacers
2. Fit the guard to twin upright bracket with the supplied M10 fasteners
3. Fit the curved bracket (with the rubber strap attached) around the diff and attach to the guard with the supplied M8 fasteners





**Brown Davis Automotive Pty. Ltd.**  
ABN: 72 657 573 544

*Copyright Brown Davis Automotive Pty. Ltd. This document contains confidential and  
Technical information the property of Brown Davis Automotive Pty. Ltd.*

**UGHDCRVR1**

**3**

**Reference Images:**

